

Fast and Accurate. Do it the ...

# KWIK-WAY®

The  
First Line  
of Tilt-Tower  
Tire Changers  
to take up to  
26"  
Wheels!

## 540 Telescopic Tilt-Tower Tire Changer

**The First Tire Changer  
to Change 26" Tires  
Without Adapters**

- *Effortlessly mount up to 26" wheels* with standard equipment - no additional accessories needed
- *NEW Tecnoroller III-SL with Twin Pistons* - outperforms the competition
- *NEW Tecnoroller III-SL with Twin Rollers Plus larger Disc Roller* - smooth, easy mounting
- *Follower Arm* takes you to the next level with ease of operation
- *Telescopic tower* makes this the strongest and most versatile machine on the market
- *New bead blast system* eliminates back strain - seats bead on the most difficult wheels and tires with ease
- *Minimize Wheel Damage* - virtually nothing touches the wheel



With Kwik-Way's commitment to continuous improvement, equipment specifications, options and accessories are subject to change without notice.

# 540 Telescoping Tilt-Tower Tire Changer



## Ordering Information:

### 540 Telescopic, Tilt-Tower Tire Changer

Standard Equipment includes: *Tire Iron, Five Tower Tabs (for alloy wheel protection), Tire Lube Cup & Brush, ZEPPA (low profile Adapter), Bead Blast System, Patented Safety Strap System and Tecnoroller III-SL with Follower Arm.*

540 Telescoping Tilt-Tower Tire Changer  
with Tecnoroller III-SL & Follower Arm 540-0001-41

## Specifications

Tire Diameter	40"
Maximum Wheel & Tire Width	14"
Wheel Clamp – External	11" - 26"
Wheel Clamp – Internal	12" - 26"
Bead Breaker Force	5,500 lbs
Electrical Requirement	115 Volt (60 Hz/1Ph)



### Zeppa, Low-Profile Mounting Adapter (Standard)

- Fast, worry-free mounting
- Fits all style wheels
- Safe and easy-to-use



### Safety Strap System (Standard)

- Unique safety device prevents the ejection of a tire in case of an explosion
- Ensures maximum safety during tire inflation



### Bead Blast System (Standard)

- Less effort seating the bead
- Eliminates back strain - seats bead on the most difficult tires and wheels



### Mount/Demount Head Cover (Optional)

- Minimize damage to wheels

### NEW Follower Arm (Standard)

- Hand-free mounting of the most difficult tires



### NEW 241 Tire Lift (Optional)

- Assists in loading wheels on tire changers and wheel balancers
- Minimizes back strain
- Easy to operate

### NEW Tecnoroller III-SL (Standard)

- NEW Double Piston Power - exclusive to the Tecnoroller III-SL
- Roller design allows the upper bead to be pressed into the drop center during mounting *and* easy removal of the lower bead when demounting
- Speeds the process to effortlessly mount & demount without scratching the wheel

## Standard Accessories

Tire Iron	502-1026-83
Mount/Demount Inserts ( <i>alloy rim protectors</i> ) - set of 5	502-1016-08
Tire Lube Reservoir and Brush	502-0013-52
Zeppa Low-Profile Assist	502-1020-95
Patented Tecnoroller III-SL	508-5000-03
Follower Arm	508-5000-02

## Optional Parts & Accessories

241 Two-For-One Tire Lift	241-0000-01
Mount/Demount Inserts ( <i>alloy rim protectors</i> ) - set of 5	502-1016-08
Kwik-Change, Hi-Performance Nylon Mount/Demount Head Adapter Kit	502-7000-00
Replacement Nylon Mount/Demount Head ( <i>requires use of Kit</i> )	502-7000-10
Bead Breaker Protective Cover ( <i>alloy wheels</i> )	502-1018-00
Mount/Demount Head Cover	502-1027-25

Call for a Distributor near you

# 1-800-553-5953

KW Products • 500 57th Street • Marion, IA 52302 USA  
319-377-9421 • (FAX) 319-377-9101 • [www.kwik-way.com](http://www.kwik-way.com)